

MVS-1U-CASE

1U MVS platform



Description

MVS- 1U-CASE modular platform offers high-density delivery of HD, SD and HDMI modular display solution. The 1U platform unit supports up to 6 modules. The unit supports up to 20+1 video input channels. And the output module provides 1 HDMI output and 1 VGA output.

Dual redundant power supplies are available. It provides a Xio-BUS. Using standard SNMP protocol, the unit can be managed by a centralized monitoring and management system.

Frame Image



Specifications

1U modular platform:

Up to 6 modules

Power: Dual redundant power supplies

Input: 100-250V 50/60Hz 2.5A

Power consumption: Max 2x120W (1U)

Temperature:

Operation temperature: 0-40°C

Store temperature: -30-+75°C

Dimension: 438 x 368 x 44mm

Headquarter: Gefei Tech. Co., Ltd

A-603 Power Creative Plaza, NO.1 Shangdi E. Rd, Haidian District, Beijing, P.R.China

International Sales: Gefei International Co.

266 Sargent rd., Boxborough, MA 01719, USA

Tel:+86(010)58858188 Fax: +86(010)58858189

Tel: +1(508) 473-3080 Fax: +1 (978) 264-0789

Web: www.gefei-tech.com Email: sales@gefei-tech.com